

60,130-1899; 03MRA0388

IN THE CLAIMS

1. (Currently Amended) A disc brake comprising:
an actuation mechanism being movable member for moving to apply a braking force;
a pair of pistons movable upon receipt of said braking force to force a brake pad into contact with an item to be braked;
an adjustment mechanism for adjusting the location of said pistons to take up clearance with wear in said brake pad; and
a force sensor for sensing a reaction force to said braking force, and identifying a point of force application increase indicative of initial contact of said brake pad with the item to be braked, said force sensor sending a signal to an electric control for said adjustment mechanism.
2. (Currently Amended) The A-disc brake as set forth in claim 1, wherein said actuation mechanism is an eccentric shaft, said eccentric shaft driving at least one bearing to in turn force said pistons and said brake pad toward the an-item to be braked.
3. (Currently Amended) The A-disc brake as set forth in claim 2, wherein said force sensor is located to receive a reaction force from said eccentric shaft and said eccentric shaft applying said reaction force to said bearing.
4. (Currently Amended) The A-disc brake as set forth in claim 3, wherein a bearing cup supports said bearing and said eccentric shaft, said force sensor being placed on an opposed side of said bearing cup from a surface that supports said bearing and said eccentric shaft.

60,130-1899; 03MRA0388

5. (Currently Amended) The A-disc brake as set forth in claim 4, wherein said force sensor and said bearing cup are received in a cavity in a housing for said disc brake.
6. (Currently Amended) The A-disc brake as set forth in claim 4, wherein said force sensor has an outer cover, and a thin anvil member is placed between said outer cover and said force sensor, said thin anvil member transmitting said reaction force from said outer cover to said force sensor, and said thin anvil member being operable to limit a total force applied to said force sensor.
7. (Currently Amended) The A-disc brake as set forth in claim 1, wherein said force sensor is an electric sensor receiving a current and having a resistance that varies with the force applied to said force sensor.
8. (Currently Amended) The A-disc brake as set forth in claim 7, wherein said force sensor includes a protective cover between a member which applies said reaction force and an electric portion of said force electric sensor which receives said current.
9. (Currently Amended) The A-disc brake as set forth in claim 8, wherein a relatively thin anvil member is placed between said protective cover and said electric portion, said thin anvil member transmitting force from said protective cover to said electric portion, and said thin anvil member limiting the amount of total force applied to said electric portion.

60.130-1899; 03MRA0388

10. (Currently Amended) A disc brake comprising:
- an actuation mechanism being movable ~~for moving~~ to apply a braking force;
 - a pair of pistons movable upon receipt of said braking force to force a brake pad into contact with an item to be braked;
 - an adjustment mechanism for adjusting the location of said pistons to take up clearance with wear in said brake pad; and
 - a force sensor for sensing a point of force application increase indicative of initial contact of said brake pad with the item to be braked, said force sensor sending a signal to an electric control for said adjustment mechanism, said force sensor being an electric sensor receiving a current and having a resistance that varies with the force applied to said sensor.
11. (Currently Amended) The A-disc brake as set forth in claim 10, wherein said force sensor includes a protective cover between a member which applies said force to said force sensor and an electric portion of said force ~~electric~~ sensor which receives ~~said~~ current.
12. (Currently Amended) The A-disc brake as set forth in claim 11, wherein a relatively thin anvil member is placed between said protective cover and said electric portion, said thin anvil member transmitting force from said protective cover to said electric portion, and said thin anvil member limiting the amount of total force applied to said electric portion.

60,130-1899; 03MRA0388

13. (Currently Amended) The A-disc brake as set forth in claim 10, wherein said actuation mechanism is an eccentric shaft, said eccentric shaft driving at least one bearing to in turn force said pistons and said brake pad toward the an-item to be braked.

14. (Currently Amended) The A-disc brake as set forth in claim 13, wherein said force sensor is located to receive a reaction force from said eccentric shaft and said eccentric shaft applying said reaction force to said bearing.

15. (Currently Amended) The A-disc brake as set forth in claim 14, wherein a bearing cup supports said bearing and said eccentric shaft, said force sensor being placed on an opposed side of said bearing cup from a surface that supports said bearing and said eccentric shaft.

16. (Currently Amended) The A-disc brake as set forth in claim 15, wherein said force sensor and said bearing cup are received in a cavity in a housing for said disc brake.

17. (Currently Amended) The A-disc brake as set forth in claim ~~16~~ 12 wherein said thin anvil member is a compliant member whose deformation is limited by the cavity ~~recess in the bearing cup/housing structure.~~

18. (Currently Amended) A disc brake comprising:
an actuation mechanism being movable ~~for moving~~ to apply a braking force;

60,130-1899; 03MRA0388

a pair of pistons movable upon receipt of said braking force to force a brake pad into contact with an item to be braked, said actuation mechanism including an eccentric shaft, said eccentric shaft driving at least one bearing to in turn force said pistons and said brake pad toward the item to be braked, a bearing cup supporting said bearing and said eccentric shaft, said bearing cup received in a cavity in a housing for said disc brake;

an adjustment mechanism for adjusting the location of said pistons to take up clearance with wear in said brake pad; and

a force sensor for sensing a point of force application increase indicative of initial contact of said brake pad with the item to be braked, said force sensor sending a signal to an electric control for said adjustment mechanism, said force sensor being an electric sensor receiving a current and having a resistance that varies with the force applied to said force sensor, said force sensor being positioned between said bearing cup and said cavity ~~of said housing~~, said force sensor being an electric sensor receiving a current and having a resistance that varies with the force applied to said force sensor.

19. (Currently Amended) The A-disc brake as set forth in claim 18, wherein said force sensor includes a protective cover between said bearing cup and an electric portion of said electric sensor which receives said current.

20. (Currently Amended) The A-disc brake as set forth in claim 19, wherein a relatively thin anvil member is placed between said protective cover and said electric portion, said thin anvil

60,130-1899, 03MRA0388

member transmitting force from said protective cover to said electric portion, and said thin anvil
member limiting the amount of total force applied to said electric portion.